

Your mobility has turned a corner with the Zero Turn 8, an innovative scooter equipped with iTurn TechnologyTM, enabling you to maneuver this scooter through small spaces and around tight corners! Plus, enjoy full lighting, plenty of storage and a USB charger.







Specifications

Weight Capacity	23 st 3 lbs (147 kg)
Maximum Speed ¹	Up to 4 mph
Ground Clearance ³	33 mm (1.3") at motor
Turning Radius ³	948 mm (37.25")
Overall Length ³	1162 mm (45.75")
Overall Width ³	525 mm (20.75")
Max. Obstacle Climb	30 mm (1.25")
Drive Tyres	Front: 178 mm (7") - solid Rear: 229 mm (9") - solid
Suspension	CTS Suspension front & rear
Total Weight Without Batteries ^{3, 4}	54 kg (120 lbs)
Heaviest Piece When Disassembled ³	21.7 kg (47.8 lbs)
Drivetrain	24 volt DC motor
Dual Breaking System	Regenerative & electromechanical
Battery Requirements ³	2 x 22 Ah batteries
Battery Weight ⁴	15 kg (32 lbs) each
Battery Charger	3.5 amp off-board
Colour	Fire Opal, Onyx Black, Pearl White, Pewter, Sapphire Blue, Green Moonstone



Features

- USB device charging port
- Front and rear LED lighting
- Wrap around delta tiller
- Innovative iTurn technology
- Comfort-Trac Suspension
- Exclusive & stylish low profile tyres
- Convienient front basket

Also available in:

- Fire Opal
- Onyx Black
- Pearl White
- Pewter
- Sapphire Blue
- Green Moonstone



NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or $-3\,\%$. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tyre condition. This specification can be subject to a variance of (4, or 2, 10%).

be subject to a variance of (+ or -) 10%.
2 Includes standard seat weight.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

this specification can be subject to a variance of (+ or -) 3%.

Battery weight may vary based on battery manufacturer.